

ISOLATION TRANSFORMER



INDOOR ISOLATION TRANSFORMER
Protecting you from the worst electrical problems.

Three Phase 15 kVA - 500 kVA

Made In The USA 

Peak Current Power:

Today's systems draw alternating current in peak, non linear mode. Ordinary power conditioners typically have a high forward transfer impedance, which causes sine wave distortion. DSPM has low impedance that minimizes this distortion.

Protection Against Electrical Noise:

Electrical noise consists of spurious electrical signals which enter power lines from such sources as lightning, utility network switching and the operation of countless electrical devices.

Noise is so preventable that it accounts for nearly 90% of all problem causing power disturbances.

Power line noise is transmitted in two different forms, common-mode noise and transverse-mode (normal-mode) noise.

DSPM utilizes Faraday shields to achieve -120dB of common-mode noise attenuation. The isolation transformer also achieves -20dB per decade transverse (normal) mode noise attenuation.

Solutions to Power Line Disturbances:

Common-Mode Noise Protection:

This type of noise is a voltage disturbance found between both current carrying leads and the common ground wire.

Transverse-Mode Protection:

Transverse-mode noise is not as easily eliminated as common-mode noise. Transverse voltage can be found on the secondary winding of power transformer, providing significant transverse-mode noise attenuation.



ISOLATION TRANSFORMER



- *Standard Power Levels.....15, 30, 50, 75, 100, 125, 150, 175, 200, 225, 250, 300, 400 and 500 kVA
 - *Input Voltage208 or 480 VAC
 - *Input Voltage Range.....+5%, -10% @ 2.5% Manual Taps
 - *Output Voltage.....208Y/120 or 480Y/277 VAC
 - *Output Frequency Range.....50 to 60 Hz, ±5%
 - Output Impedance.....3 to 5%
 - Response Time.....<200 nanoseconds
 - Common-Mode.....-120 dB Noise Attenuation
 - Normal-Mode.....-20 dB/decade
 - Overload (In-rush).....200% of a full load for 30 minutes, 1000% of a full load for 1 cycle
 - Load Power Factor.....0.3 leading or lagging to unity
 - Efficiency.....96% at full loads, and 98.5% at light loads
 - Audible Noise.....<45dB measured on Response Curve "A"
 - Operating Temperature.....0° to 40°C (32° to 104°F)
 - Storage Temperature.....-15° to 50°C (5° to 122°F)
 - Humidity.....5 - 95%, Non-condensing
 - Operating Temperature.....up to 10,000 ft.
 - Cabinet.....NEMA 1 Indoor Cabinet
 - *Consult factory for others.
- Specifications subject to change without notice.

Isolation Transformer Series	Power Rating	Cabinet Dimensions			Weight
		kVA	W	H	
ISO3 (Consult factory for others)	15	21"	28"	14"	300
	30	26.5"	32"	17"	420
	50	26.5"	32"	17"	530
	75	31.5"	40.5"	21.75"	670
	100	31.5"	40.5"	21.75"	800
	125	31.5"	40.5"	21.75"	890
	150	40.5"	51.5"	26.5"	970
	175	40.5"	51.5"	26.5"	1150
	200	40.5"	51.5"	26.5"	1300
	225	40.5"	51.5"	26.5"	1400
	250	40.5"	51.5"	26.5"	1500
	300	40.5"	51.5"	26.5"	1700
400	50.5"	66"	32"	2350	
500	50.5"	66"	32"	2550	

Options:

- SSS - Secondary Surge Suppression
- IF - Input Filter
- IOF - Input/Output Filter
- CMNA140 - Common Mode Noise Attenuation -140dB
- CMNA152 - Common Mode Noise Attenuation -152dB
- HIT - High Isolation Transformer
- HCR - Harmonic Reduction
- STU3 - Onsite Startup
- EW - Extended Warranty



Email: info@DSPManufacturing.com
 1921 S. Quaker Ridge Place
 Ontario, CA 91761
 Ph: 1.877.DSPM POWER
 1.877.377.6769
 Fax: 909.930.3335

Represented by: